

Series LHP-150 TO-247

150 W Thick Film Resistor for high-frequency and pulse-loading applications


A Miba Group Company

1/1

EBG Resistor offers the completely encapsulated and insulated TO-247 package for low ohmic value and Non-Inductive design for high-frequency and pulse-loading applications. Ideal use for power supplies. The LHP-150 series is rated at 150 W mounted to a heat sink.


Features

- 150 W operating power
- TO-247 package configuration
- Resistor package completely insulated from heat sink
- Non-Inductive design



Technical Specifications

Resistance value	0.2 Ω ≤ 1 MΩ
Resistance tolerance	±5 % to ±10 % ±0.5 % on special request for limited ohmic values
Temperature coefficient	±150 ppm/°C (+25°C to +105°C, ref. to +25°C)
Power rating	150 W at 25°C bottom case temperature
Maximum operating voltage	700 V DC
Dielectric strength	1800 V AC
Insulation resistance	min. 10 GΩ
Momentary overload	2 times rated power, but no more than 1.5 time max. continuous operating voltage, last 5s, ΔR ≤ ±(0.5% R + 0.001Ω)
Load life	2,000 hours at rated power, MIL-R-39009D ΔR ≤ ±(1.0% R + 0.001Ω)
Moisture resistance	MIL-Std.-202, method 106, ΔR ≤ ±(0.5% R + 0.001Ω)
Thermal shock	MIL-Std.-202, method 107, Cond. F ΔR ≤ ±(0.3% R + 0.001Ω)
Terminal strength	MIL-Std.-202, method 211, Cond. A (pull test) 2.4 N ΔR ≤ ±(0.2% R + 0.001Ω)
Vibration, high frequency	MIL-Std.-202, method 204, Cond. D ΔR ≤ ±(0.2% R + 0.001Ω)
Working temperature	-55°C to +175°C
Lead material	tinned copper
Weight	~4,2 g



Derating (thermal resist.) LHP-150:
1.00 W/K (1.0 K/W)

Without a heat sink, when in open air at 45°C, the LHP-150 is rated for 4.5 W.

How to make an order

LHP-150_Ohmic Value_Tolerance

For example:

LHP-150 50R 5%


Application Standard

- IEC60115-1 : 2001 (GB/T5729-2003)
- MIL-STD-202
- MIL-R-39009D
- AEC-Q200

Soldering Note:

During surface mount soldering, the soldering temp. profile **must not** cause the metal tab of this device to **exceed 245°C**.

Dimensions in mm [inches]



The above spec. sheet features our standard products. For further options please contact our local EBG representative or contact us directly.

sales@ebg-resistors.com · sales@ebg-us.com