



Turn-key HV Power Solutions

***Voltages from 5,000V to 50,000V
Power levels from 60kW to 1MW +
Ultra High Power Density
Full Local and Remote Controls
Modular/Scalable System Designs***



TDK-Lambda
Trusted • Innovative • Reliable

www.us.lambda.tdk.com

Turn-key High Voltage Power Solutions

ALE's Compact Turn-key High Voltage Power Systems, build on over 20 years of successfully designing and delivering multi-kilowatt DC power solutions to meet the demands of the most challenging applications. Extensive use of standard building blocks allows maximum system design flexibility and performance, while minimizing cost and delivery time.

Our modular and scalable design approach uses multiple standard ALE 303 series 50kW power modules to deliver raw high voltage DC power for the system. The outputs of each 303 power module are combined using a simple Junction box which can also accommodate any necessary output filtering and voltage/current feedback required. The complete system and individual power module outputs are centrally controlled by a Master Controller which offers both local and remote user interfaces.

The Master Controller generates all control signals required by each of the 303S power modules, and enables both local or remote user control of the system output voltage and current. The use of a multi-phase variable frequency control technique, results in low output voltage ripple without the need for large output energy storage filter capacitors. The controller interfaces to each 303 power module (or bank of 303 power modules), and to the Junction Box to provide system output voltage and current feedback, and operating status.

Each power module comprises a single model 303S water-cooled power supply. The 303S is a proven 50kW rated DC power supply which can be offered with any output voltage between 5kV and 50kV. The total number of 303S modules required in the system is determined by the overall power requirements, with one module for every 50kW of power (one per 40kW with 400VAC input). Since the overall design is 100% scalable, there is no theoretical limit to the number of 303 supplies that can be connected in parallel, and hence very high power ultra compact systems can be built using standard modules.

A Junction Box is used to combine the high voltage outputs from the individual power modules, and also serves to provide precision voltage and current feedback signals to the Master Controller. The Junction Box can also be used to house any filter or output protection components required. Filters can be as simple as a ripple reduction capacitor, or more complex multi-stage LC filter when ultra-low stored energy and ripple are required.

The modular and scalable design approach described enables TDK-Lambda to offer Compact Turn-key power solutions with average output powers from as little as 60kW, to over 1MW using the same basic proven building blocks. Call our High Voltage Product Manager, Andy Tydeman at +1-732-795-4149 to discuss your specific power requirements, or to learn more.

Features

- Power levels from 60kW to 1MW and higher
- Voltages from 5,000V to 50,000V
- Turn-key Fully Integrated Systems
- 100% Modular/Scalable Design
- Ultra Compact Mechanical Layout
- Low Ripple
- Low Stored Energy
- No requirement for crowbar load protection
- High Efficiency
- Excellent Power Factor
- Water-cooled with zero oil
- Local & Remote Controls
- Complete System or bare bones versions

Applications

- Cyclotrons
- Microwave Tube Beam Power
 - Gyroton
 - Klystron
 - Magnetron
 - TWT
 - IOT
- Radar Systems
- Raw HVDC Power
- High Power Amplifiers
- Precipitators

Specification

Average Continuous DC Power	Available from 60kW to 1MW+
Output Voltage Range	Models available from 5kV to 50kV, variable from 10-100% of rated voltage
Output Current	Variable from 10-100% of rated current
AC Input Voltage	480VAC 3Ø standard, 400VAC 3Ø + N optional
Polarity	Available as fixed Positive or Negative. Optional floating return.
Power Factor	Passive PFC better than 0.92 at full load and nominal AC line
Efficiency	Better than 85% at full load and nominal AC line
Accuracy	1% standard, 0.1% optional
Stability	100ppm per °C standard, 10ppm per °C optional
Stored Energy	Less than 50J, 10J optional
Ripple	1% of rated voltage peak to peak, 0.01% optional
Line/Load Regulation	Better than 0.1%, 0.01% optional
Cooling	Water cooled, 2US GPM flow per 50kW module, Min. temp 15°C, Max. Temp 35°C
Ambient Temperature	Storage: -40 to +85°C. Operating: +5 to +45°C
Humidity	10-90%, non-condensing
Protection	Open/short circuits, Overloads, Arcs, Overvoltage, Overcurrent
Load ARC Response	Output current shut down in less than 50µs
Local Control/Indicators	Power ON/OFF switch HV ON/OFF push buttons Local/Remote keyswitch View Set push button 10-Turn Output voltage potentiometer 10-Turn Output current potentiometer Adjustable Overvoltage trip point Adjustable Overcurrent trip point Digital voltage and current displays LED status indicators
Remote Control	Fully isolated analog voltage and current programming and readback Isolated digital HV ON/OFF & Inhibit inputs Isolated digital status readback/monitoring
Options	Fully integrated turn-key rack mounted system with all cooling and control cables Bare bones system for customer installation/integration High stability output (10ppm/°C) High accuracy (0.1% or 0.01%) Low Output stored energy (10J or less) Low Ripple (0.01% or better) Custom LC output filter Load/Line regulation better than 0.001% Custom HV connectors Floating HV return
Mechanical - Master Controller (1 per system) - Power Module (1 per 50kW) - Junction Box (1 per system)	4U (178mm) high, 19" (483mm) wide, 17" (432mm) deep, Weight: 25lbs (11kg) 7U (311mm) high, 19" (483mm) wide, 24" (610mm) deep, Weight: 300lbs (136kg) Approx 8U (356mm) high, 19" (483mm) wide, 24" (610mm) deep, Weight: 50lbs (23kg). Size is dependant on system power and performance, data given is typical. Example 300kW 20kV system dimensions - 68" (1727mm) high including casters, 44.25" (1124mm) wide, 38.5" (978mm) deep. Weight: Approx 2500lbs (1140kg)
All specifications subject to change without notice	

GLOBAL HIGH VOLTAGE NETWORK

NORTH AMERICA

TDK-Lambda Americas Inc., Programmable and High Voltage
405 Essex Rd. Neptune, NJ 07753
Tel: +1-732-795-4100, Fax: +1-732-922-1441
E-mail: andy.tydeman@us.tdk-lambda.com
Web: www.us.lambda.tdk.com

CANADA

ACA TMatrix
5805 Kennedy Road
Mississauga, Ontario L4Z 2G3
Tel: +1-800-665-7301 Fax: +1-905-890-1959
E-mail: lambda@aca.ca, Web: tmatrix.com

UK

Pulse Power & Measurement Ltd.
65 Shrivenham Hundred Business Park
Watchfield, Swindon
Wiltshire, SN6 8TY
Tel: +44-1793-784389, Fax: +44-1793-784391
Email: sales@ppm.co.uk, Web: www.pmpower.co.uk

IRELAND

FRANCE

TDK-Lambda France
3 Avenue du Canada, Parc Technopolis - Bâtiment Sigma
91940 Les Ulis
Tel: +33 1 60 12 71 65, Fax: +33 1 60 12 71 66
Email: france@fr.tdk-lambda.com
Web: www.emea.lambda.tdk.com/fr

BELGIUM

SPAIN

NETHERLANDS

LUXEMBOURG

GERMANY

Guth High Voltage GmbH
Spitzenbergstrasse 6
D – 73084 Salach
Tel: +49-7162-948930, Fax: +49-7162-9489399
Email: kontakt@guth-hv.de, Web: www.guth-hv.de

AUSTRIA

SWITZERLAND

ITALY

TDK-Lambda France Sas Succursale Italiana
Via Giacomo Matteotti 62,
20092 Cinisello Balsamo (MI)
Tel: +39-02-6129-3863, Fax: +39-02-6129-0900
Email: info.italia@it.tdk-lambda.com
Web: www.emea.lambda.tdk.com/it

SCANDINAVIA

BALTICS

Divisoft AB
Sturevägen 3, SE-177 56 Järfälla
Tel: +46 8 540 248 09, Fax: +46 8 501 096 53
Email: iain@divisoft.se, Web: www.divisoft.se

ISRAEL

RUSSIA

UKRAINE

TDK-Lambda Israel Ltd.
56th Hachroshet st., Industry zone, Karmiel, 2161401
Tel: +972-3-9024-333, Fax: +972-3-9024-777
Email: info@tdk-lambda.co.il, Web: www.emea.lambda.tdk.com/il

BRAZIL

Suplitec
Rua Sena Madureira 455, Belo Hte - 31340-000
Tel: +55-31-3498 1177, Fax: +55-31-3441 0841
Email: vendas@suplitec.com.br, Web: www.suplitec.com.br

MEXICO

AcMax De Mexico
Calle Rosas No. 139 Col. Bugambilias, Puebla, Pue. C.P. 72580
Tel: +52-800-211-0060, Fax: +52-264-1445
Email: edaena@acmax.mx, Web: www.acmax.mx

JAPAN

KOREA

Electronics Optics Research, Ltd
4-26-19 Koenji-Minami
Suginami-ku, Tokyo 166-0003
Tel: +81-333-145699, Fax: +81-333-142333
Email: imamura@eor.jp, Web: www.eor.jp

CHINA

TDK-Lambda Shanghai Office
5th Floor Kehui Tower, 1188 Qinzhou Road (North),
Xuhui District, Shanghai, 200233 P.R. China
Tel: +86-21-64850777, Fax: +86-21-64850666
Email: sales-sh@cn.tdk-lambda.com
Web: www.lambda.tdk.com.cn

MALAYSIA

TDK-Lambda Malaysia
Lot 709, Nilai Industrial Estate,
71800, Nilai,
Negeri Sembilan, Malaysia
Tel: +60-3-7957-8800 Fax: +60-3-7958-2400

SINGAPORE

PHILIPPINES

THAILAND

TDK-Lambda Singapore
1008 Toa Payoh North # 06-01/08
Singapore 318996
Tel: +65-6251-7211 Fax: +65-6250-9171
Web: www.sg.lambda.tdk.com

INDIA

TDK-Lambda India
No.989, 1st Cross, 2nd Floor, 13th Main,
HAL 2nd Stage, Bangalore, Karnataka, India – 560 008
Tel: +91-80-43550500, Fax: +91-80-43550501
Email: mathew.philip@in.tdk-lambda.com

SOUTH AFRICA

PaR Systems (Pty) Ltd.
Pretoria, South Africa
Tel: +27-12-5480370, Fax: +27-12-5480447
Email: lasers@par.com
Web: www.par.com/technologies/pulsed-co2-lasers



TDK-Lambda Americas Inc. 405 Essex Road, Neptune, NJ 07753 USA
Tel: +1 732 795 4100
www.us.lambda.tdk.com

93 008 110 Rev D